



## **ACS Valves Quick Take Apart Feeder- ON RAILS**

ACS Quick Clean Feeder is used for pneumatic conveying and bulk material handling applications and is available in light, medium and heavy duty models with square or round flanges. The quick clean feeder is available in the CI, MD, DR-S, AF Feeder, and S-Pellet Feeder models. Valves can handle pressure up to 15 PSI. Valves are available in sizes 4" through 16". Precision-machined internal surfaces for an effective airlock seal. Available in cast iron or stainless steel up to #4 polish (150-180 grit).

Check out the Quick Clean Feeder video at [www.powderandbulk.com](http://www.powderandbulk.com) (Video Center - search ACS Valves).



## **Quality Done Right the First Time**



Each rotary valve goes through a thorough inspection process before leaving ACS. Every valve is run for 30 minutes to ensure everything is working correctly. The clearances are checked on the tips and sides of the rotor. Once the testing and inspection is completed, it is recorded on an inspection sheet. Safety stickers are put on all the valves, as well as rotation stickers. Our inspectors take a photo of each valve, and then it is securely fastened to a skid with steel banding and protective shrink wrap.

We complete this inspection process with each and every valve, because it is very important to us that your rotary valve is *designed for your success.*

If you would like any further details on the topics discussed above, please contact our offices by phone at **800-655-3447**, or by e-mail at [sales@acsvalves.com](mailto:sales@acsvalves.com). Many thanks for all your support and interest in our Rotary Airlock Feeders.

**V02-0609**